

ENO-STEAM

STEAM GENERATORS

MAIN TECHNICAL DATA

Power supply	400 V - 50/60 Hz
Boiler volume	25 l - 51 l
Boiler power	18 kW / 24 kW / 36 kW / 48 kW
Steam temperature	160° C
Steam pressure	from 0,5 to 6,0 Bar
Dimensions	540x540x1100 mm
Weight	90/110 kg



STANDARD

Automatic water refill



Water mains connection

5-pole plug



OPTIONAL

70 lt stainless steel water tank with float

Pressure reducer
0,5" / 1"

Cart Mini/Max

Versions available

- Eno-Steam 18 kW
- Eno-Steam 24 kW
- Eno-Steam 36 kW
- Eno-Steam 48 kW

*The steam generators don't include accessories

Optional

- 70 lt stainless steel water tank
- Cart Mini
- Cart Max
- Pressure reducer from 0,5 to 6,0 Bar (0,5")
- Pressure reducer from 0,5 to 6,0 Bar (1")

Steam generators accessories

70 lt stainless steel tank with float

cod. BATTIS.1370



Cart

cod. CARR.ENOSTEAM.PC

cod. CARR.ENOSTEAM.GR



Mini

Max (vers. generator + water tank)

Pressure adjustment from 0,5 to 6,0 bar

cod. MODU.RIDU.0.5/6

cod. MODU.RIDU.0.5/6.1



0,5"

1"

Accessories for use

Eno-Steam Kit



cod. KIT.ENO-STEAM5

5 mt

cod. KIT.ENO-STEAM6

6 mt

cod. KIT.ENO-STEAM8

8 mt

cod. KIT.ENO-STEAM10

10 mt

Straight rigid lance 1050

cod. PROL.LANC.DIR.1050



Curved rigid lance 1050

cod. PROL.LANC.CUR.1050



Curved rigid lance 450

cod. PROL.LANC.CUR.450



Curved rigid lance 250

cod. PROL.LANC.CUR.250



Ø 50 brushes

cod. SPAZZ.NY.50.EVO



NYLON

cod. SPAZZ.AC.50.EVO



STEEL

cod. SPAZZ.BR.50.EVO



BRASS

cod. SPAZZ.AC.IX.50.EVO



STAINLESS STEEL

cod. SPAZZ.AC.TX.50.EVO



TYNEX

Rectangular brush for steam

cod. PORT.SPPV40051



Eno-Steam pipe



cod. TUB.FLESS.4

4 mt

cod. TUB.FLESS.6

6 mt

cod. TUB.FLESS.8

8 mt

cod. TUB.FLESS.10

10 mt

GAROLLA connector

cod. ATT.GAROLLA.40



cod. ATT.GAROLLA.50

DIN connector

cod. ATT.DIN.40



cod. ATT.DIN.50

Barrigue washer

cod. LAVABARRIQUE.NOV

