

HIGH-STEAMER

STEAM GENERATORS

MAIN TECHNICAL DATA

Power supply	400 V - 50/60 Hz
Boiler volume	25 l - 51 l
Boiler power	18 kW / 24 kW / 36 kW / 48 kW
Steam temperature	160° C
Steam pressure	9,0 Bar
Dimensions	540x540x1100 mm
Weight	90/110 kg



DI SERIE

Automatic water refill



Water mains connection

5-pole plug



Hot water supply



OPTIONAL

70 lt stainless steel water tank with float

Cart Mini/Max

Versions available

- High-Steamer 18 kW.....
- High-Steamer 24 kW.....
- High-Steamer 36 kW.....
- High-Steamer 48 kW.....

*The steam generators don't include accessories

Optional

- 70 lt stainless steel water tank
- Cart Mini
- Cart Max.....

Steam generators accessories

70 Lt stainless steel tank with float

cod. BATTIS.1370



Cart

cod. CARR.ENOSTEAM.PC

cod. CARR.ENOSTEAM.GR



Mini

Max (vers. generator + water tank)

Accessories for use

EVO PLUS KIT



cod. KITE.EVO.PLUS.4

cod. KITE.EVO.PLUS.6

cod. KITE.EVO.PLUS.8

cod. KITE.EVO.PLUS.10

4 mt

6 mt

8 mt

10 mt

Straight rigid lance 1050

cod. PROL.LANC.DIR.1050



Curved rigid lance 1050

cod. PROL.LANC.CUR.1050



Curved rigid lance 450

cod. PROL.LANC.CUR.450



Curved rigid lance 250

cod. PROL.LANC.CUR.250



Ø 50 brushes

cod. SPAZZ.NY.50.EVO

cod. SPAZZ.AC.50.EVO

cod. SPAZZ.BR.50.EVO

cod. SPAZZ.AC.IX.50.EVO

cod. SPAZZ.AC.TX.50.EVO

cod. MENIK.Q05102778

cod. MENIK.Q05102779



NYLON



STEEL



BRASS



STAINLESS STEEL



TYNEX



Ø 200

Ø 300

Twister

Cleaning accessories for conveyor belts

Robo-Steam



Steam-Belt

